

Powerful PA speaker fits in various music scene with deep bass.

Woofers use reliable paper cone Made in Japan.

Box hanging bracket, arranged so as to be installed in all of the PA and KTV.

Rotatable BMB logo plate and woofer/tweeter make it possible to set up the speakers anywhere.

1. PA type spealer, for large Karaoke room or stage event.

2. It matches not only karaoke but also music of various genres.







The Tweeter

The vibrating membrane of compression drivers, uses titanium nitride material made in Japan.

By ultra hardness nitriding the titanium foil it is possible to play the ultra high above the audible frequency range that is essential for a good music playback.



The Tweeter

The voice coil is a large diameter of \$45mm, and have excellent power handling, exerts a strong driving force. Also, the electric wire by adopting those molded pure aluminum wire in flat shape, and realize a highly efficient


driver with good transient response lightweight. Together with lightweight titanium nitride vibrating membrane, can be reproduced to the super-high region.



The Woofer

The voice coil is a large diameter of φ75mm (CSS-2010:φ 75mm), and have excellent power handling, exerts a strong driving force.


Wire is the φ0.37mm thick aluminum wire (CSS-2010: φ0.32 aluminum wire). Lightweight and excellent transient response, and provides a bass with a sense of speed, the sound quality without distortion.





Highly reliable paper cone Made in Japan

MADE IN JAPAN





CSS-2012 [SE] [12"]

2 Ways 2 Speakers System Woofer Unit "300mm(12inch) Paper Cone Type × 1unit With 65mm(2.5inch) Coil × 1unit" Tweeter Unit 26mm Throat,44.4mm Coil Diaphragm Assembly Type × 1unit Freq. Response 50Hz~20.000Hz(±3dB) Sensitivity Max SPL Peak Max SPL Continuous Max Input Power 500W(Public Addresses speaker type) Rating Input Power 800W(DAP-8000) Recommended Amplifier **HF Protections** Poly Switch Circuit Breaker Horizontal Coverage Vertical Coverage Neutrik SpeakON® NL4MP x 2 Connector Impedance

 $380(W) \times 615(H) \times 386(D)$


24.6 kg per piece

Enclosure Material 15mm Plywood construction 5.5mm Custom Hexagon perforated steel grille Pole Mount φ36mm bottom support base

Dimensions (mm)



2 Ways 2 Speakers "250mm(10inch) Paper Cone Type x 1unit With 60mm(2.3inch) Coil × 1unit" 26mm Throat,34.4mm Coil Diaphragm Assembly Type × 1unit 55Hz~20.000Hz(±3dB) 300W(Public Addresses speaker type) 500W(DAP-5000) Poly Switch Circuit Breaker Neutrik SpeakON® NL4MP x 2 315(W) × 527(H) × 335(D) 16.6 kg per piece 15mm Plywood construction 5.5mm Custom Hexagon perforated steel grille Paint Finish



φ36mm bottom support base